

## 6491B LS0H

LSOH Thermosetting Insulated Single Core Cable

designed for installation within conduit, trunking or inside fixed protected environments

\*Available in Brown, Blue, Black, Grey, Green/Yellow\*



## 6491B LSOH CABLE DESCRIPTION

6491B cables are designed to be used in installations where smoke and acid gas emissions pose a major hazard in the event of a fire. They are intended for installation in conduit and for fixed, protected installations. Also suitable for lighting fittings, appliances and switch gear installations.

CONDUCTOR: Class 2 Stranded Copper

INSULATION: LSOH (Low Smoke Zero Halogen)

VOLTAGE RATING: 450/750V TEMPURATURE RATING: -15°C to +90°C

OUTER SHEATH: LSOH (Low Smoke Zero Halogen), UV Resistant

FLAME RETARDENT: IEC/EN 60332-1-2

HALOGEN FREE: IEC/EN 61034-1/2, IEC/EN 60754-1/2

STANDARDS: EN 50525-3-41, EN 60228

APPROVALS: BASEC

CPR RATING: Eca to EN 50575:2014+A1:2016

Part Number	Weight kg/km	O/D mm	Glands to Suit * A2	Glands to Suit * A2
			Brass	Nylon
1.5mm 6491B	22	3.1	20/16	16
2.5mm 6491B	33	3.7	20/16	16
4.0mm 6491B	49	4.1	20/16	16
6.0mm 6491B	69	4.7	20/16	16