

20W LED Task Light

Safety Instructions

- Ensure the power supply is switched off before servicing.
- Ensure that this task light is connected to a suitably earthed power supply only.
- This task light is rated for indoor use.
- This task light should be carried using the handle only. Do not carry / move the task light by the cable.
- This tasklight must be mounted on a non-flammable surface.
- Do not use this task light if it appears damaged in any way.
- This task light should be positioned so that it will not be accidentally knocked.
- This task light must be installed and used in accordance with the current edition of the IEE Wiring Regulations.

If in doubt, contact a qualified electrician.

Maintenance instructions

- There are no user serviceable parts in this fitting.
- Periodically wipe the housing and heat sinks to maintain proper heat dissipation.

Operating Instructions

- This task light is designed to be used freestanding.
- Before use, ensure that the task light and cable do not appear damaged.
- Adjust the stand to the required angle.
- Connect the task light to a suitable power supply.
- Switch the task light on by operating the push switch on the rear.
- Outlet socket on rear can be used for connecting power tools or similar equipment, or can be used to daisy chain fittings together.
- Outlet socket on rear remains live even when light is switched off.
- When using the task light, ensure that the lead does not cause an obstruction.
- Ensure task light is switched off by the rear switch before disconnecting from the supply.
- Ensure the task light is disconnected from the supply when no longer required.

Power Supply	S3040	110V-50Hz	Lamp Colour Temperature	6400K
	Lumen	2000lm	IP Rating	IP44
Lamp Type		20W SMD LED	Lead Length	3m

Deta Electrical Company Ltd.

UK: Panattoni Park Luton Road Chalton Beds. LU4 9TT UK

EU: Unit 16 Ashbourne In. Est. Ashbourne Co. Meath A84 W972 Ireland

deta.co.uk

Technical Helpline: +44(0)1582 544 548



LED Task Lights

Description

Briticent Task Light's offer a wide range of compact and portable 110V luminaires for commercial and industrial and site lighting applications.

This range includes a single and a linkable task lights.

Features

- Suitable for a range of commercial, industrial and site lighting applications
- Ideal replacement for halogen task lights
- Aluminium body with tempered glass diffuser for standard task light
- Aluminium body and high grade strong polycarbonate diffuser for linkable task light
- Linkable task lights can be daisy chained together
- Linkable unit supplied with foldaway stand with carry handle and protective rubber trim
- Standard units supplied with 1.5m power lead and 16A connector
- Linkable units supplied with 3m power lead and 16A connector
- 1-year guarantee

Technical Specification

Voltage	110V	
Frequency	50Hz	
Colour Temperature	6400K Daylight White	
Beam Angle	110°	
Light Source	Non-replacable LED's	
Lifespan	30,000 Hours	
	S3040	S2010
Wattage	20W	36W
Luminous Efficacy	100 lm/W	66 lm/W
Lumens	2000 lm	2400 lm
IP Rating	IP44	IP54
Standards	BS EN 60598-1	

No user serviceable parts

Range

S3040	20W LED Standard Task Light
S2010	36W LED Linkable Task Light

Dimensions

	Height	Width	Depth
S3040	260mm	240mm	90mm
S2010	320mm	258mm	83mm

Contact your local authority for information concerning the correct disposal of your product.